



Manufacturer of Industrial,
Protective, Marine Traffic, Automotive
& Decorative Paints

AVA™
BRS ISO 9001
HSE - ISO 14001
ISO 45001

Alkyd Anti- Corrosion (Anti- Corrosion Primer) KRS-103



Technical Data

Colors: Ochre, Orange, Green, Black, Brown, Gray, Blue

Description & Recommended Use

Alkyd Anti-corrosion is made of alkyd resin based and the highest corrosion resistant materials. This primer is applied on metal or similar surfaces as the first layer and has a suitable adhesion and durability

Specification

Easy to use
Suitable drying time
Good coverage
Suitable corrosion resistant

Technical Specifications (White) At 25°C

Flash Point: 38°C
Resin Type: Alkyd

Application Method

Brush, Spray and Roller

Application procedure

Clean the surface from any contamination and grease and wait till complete drying. Old paint's flakes must be cleaned from the surface till a flat surface achieved (If needed you can use sandpaper to remove the previous paints).
Brush must be used for cleaning the surface saltpetre
Metal surfaces must be cleaned from any rusts and filing.
Then dilute KAMEL RANG SHAKIBA Anti- Corrosion Primer with proper amount of special white spirit thinner and apply it by brush, roller or paintgun on the surface. Dilution ratio of Anti- Corrosion with thinner depends on surface and painting tools. But in normal weather conditions amount of dilution with thinner is as follows:
Brush: 20% to 40% of weight.
Paint gun :40% to 70 % of weight.
Roller: 10% to 30% of weight

Recommendations

Stir the content well before use
Add the necessary amount of white spirit thinner to primer slowly and simultaneously mix it

How To Clean Tools

After use, wash your hands and painting tools with mineral spirit or white spirit. Follow manufacturer's safety recommendations when using white spirit

Safety Points and Stronge Conditions

Keep the primer can in dry, cool place and far from the direct sunlight.



Factory: No727, Aven. Afra, Abas abad industrial state
Boostan Ave, Velenjak St, Tehran, IRAN



Phone: (+98)21-364 247 92-4
(+98)21-364 232 95-7



Manufacturer of Industrial,
Protective, Marine Traffic, Automotive
& Decorative Paints



Keep the can closed after use. It is recommended to use this product before the expire date (Maximum 12 months). While applying, use a suitable air conditioning and leave the doors and windows open. In case of epiphora, headache or other diseases, breath more fresh air or use fitted respirators (NIOSH approved) or leave the working area. Avoid eye touch, in the case of touch, wash your eyes with lots of water. Wash hands after use. If swallowed, go to medical centers.

Sanding or scraping the old Alkyd painted surfaces can cause poisonous lead dust. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure of lead or other hazardous substances requires the use of proper protective equipment, such as proper fitted respirator (NIOSH approved) and proper tools. Finally, clean up your working area.



Factory: No727, Aven. Afra, Abas abad industrial state
Boostan Ave, Velenjak St, Tehran, IRAN



Phone: (+98)21-364 247 92-4
(+98)21-364 232 95-7

