



Manufacturer of Industrial,
Protective, Marine Traffic, Automotive
& Decorative Paints



CAPITAL VINYL EMULSION PAINT KRS-105



Description & Recommended Use

Capital Vinyl Emulsion paint, is produced based on vinyl acetate Co-polymer Resin, with high quality selected pigments.

Theoretical Coverage

12- 13 m² / Lit Dry film 30 micron
7-8 m² / Lit Dry film 50 micron

Touch dry time

Max. 1 Hour

Recoating time

Min. 3 Hours

Recommended for

This paint is suitable for use on all interior surfaces such as Plaster, cement, brick, cement composition panels, and wood. This quick-drying paint is environmentally friendly, Odor free, easy to apply, excellent coverage, great adhesiveness, durable finish and very pleasant to apply.

Surface Preparation

Surface must be clean. Remove old flaking paint. If needed use plaster or cement to cover cracks and sand it to a smooth finish. Final surface must be clean and without any contaminations, dust and oil before painting.

Application methods

Brush, Roller, Spray

Thinner

WATER

How to Apply

Dilute, CRYSTAL, Vinyl Emulsion Paint, with sufficient amount of water and apply it on the surface. Dilution ratio depends on the substrate, environmental temperature and painting tools. In normal weather and standard applying condition the thinned paint may contain 35-40% of water (by weight) for applying by brush, 5-10% for applying by roller, and 45-50% for applying by spray paint gun. In order to get a smooth and consistent finish surface two or three coats may be needed. The recommended temperature for painting is over 10 °C, surface temperature of 3 above dew point and humidity less than 80%.

Cleaning Up

Clean spilled paint on the ground with warm water and soap. Clean hands and painting tools with warm water and soap. In order to prevent tools from corrosion, wash them with white spirit and dry tools immediately.



Factory: No727, Aven. Afra, Abas abad industrial state
Boostan Ave, Velenjak St, Tehran, IRAN



Phone: (+98)21-364 247 92-4
(+98)21-364 232 95-7



Manufacturer of Industrial,
Protective, Marine Traffic, Automotive
& Decorative Paints



Safety & Storage Recommendations

Keep the can in dry and cool place and away from direct sunlight. Tighten the can lid. It is recommended to use this product within 36 months from the production date. When painting, it is advisable to wear eye protection. Ensure good ventilation during application. Avoid contact with skin & eyes, In case of contact with eye, rinse immediately with plenty of water. If swallowed seek medical advice.



Factory: No727, Aven. Afra, Abas abad industrial state
Boostan Ave, Velenjak St, Tehran, IRAN



Phone: (+98)21-364 247 92-4
(+98)21-364 232 95-7

