



Manufacturer of Industrial,  
Protective, Marine Traffic, Automotive  
& Decorative Paints



## SEMI Vinyl Emulsion paint      KRS-106



### Description & Recommended Use

Vinyl Emulsion paint, is produced based on vinyl acetate Co-polymer Resin, with selected high-quality pigments.

### Theoretical coverage

7.5 – 9.5 m<sup>2</sup> / Lit Dry film 50 micron

12.5-14.5 m<sup>2</sup> / Lit Dry film 30 micron

### Touch dry time

Max. 1 Hour

### Recoating time

Min. 3 Hours

### Recommended for

This paint is suitable for use on all interior and exterior surfaces such as plaster, cement, brick, cement composition panels, and wood surfaces.

### Key Benefits

Quick-drying time, Odor free, easy to apply, excellent coverage environmentally friendly, dilutes with water and has excellent adhesiveness, washable.

### Surface Preparation

Surface must be clean. Remove old flaking paint. If needed use plaster or cement to cover cracks and sand it to a smooth finish. Final surface must be clean and without any contaminations, dust and oil before painting.

### Application methods

Brush, Roller, Spray

### How to Apply

Dilute, AQUA, Vinyl Emulsion Paint, with adequate amount of water, depending on the temperature, the substrate and painting tools and apply it on surface. In normal condition the diluting rate for applying by brush is 25 to 30%, for applying by roller is 5 to 10% and for applying by sprayer is 35 to 40%. In order to get a smooth and consistent finish surface, two or three coats may be needed. The recommended temperature for painting is + 10 °C, surface temperature of 3° above dew point and humidity less than 80%.

### Cleaning Up

Clean spilled paint on the ground with warm water and soap. Clean hands and painting tools with warm water and soap. In order to prevent tools from corrosion, wash them with white spirit and dry tools immediately.

### Safety & Storage Recommendations

Keep the can in dry, cool place and away from direct sunlight. Tighten the can lid. It is recommended to use this product within 36 months from the production date. When painting, it is advisable to wear eye protection. Ensure



**Factory:** No727, Aven. Afra, Abas abad industrial state  
Boostan Ave, Velenjak St, Tehran, IRAN



**Phone:** (+98)21-364 247 92-4  
(+98)21-364 232 95-7





Manufacturer of Industrial,  
Protective, Marine Traffic, Automotive  
& Decorative Paints



good ventilation during application. Avoid contact with skin & eyes. In case of contact with eye, rinse immediately with plenty of water. If swallowed seek medical advice.



**Factory:** No727, Aven. Afra, Abas abad industrial state  
Boostan Ave, Velenjak St, Tehran, IRAN



**Phone:** (+98)21-364 247 92-4  
(+98)21-364 232 95-7

